


5,08 mm TRIPLE-DECK 3 COLORED RAIL MOUNT TERMINAL BLOCK



GENERAL ORDERING DATA

Type	5,08 mm Triple-Deck 3 Colored Rail-Mount Terminal Block –Pin 5
Qty	45 pcs
Order no	16.505
Package weight	2,70 kg
Packaging	Box
Min. Order Qty	45 pcs
Country of origin	TURKEY

Production Code : RTKS-R 5,08-3x5



CERTIFICATES

CERTIFICATE	ISSUED BY
TS EN IEC 60947-7-4	TSE
CE	SZUTEST CO.
RoHS	İNTERTEK A.Ş.
EAC	SERCONS
DOMESTIC GOODS C.	TOBB-ISO
ISO 9001	SZUTEST CO.
ISO 14001	SZUTEST CO.
ISO 45001	SZUTEST CO.
ISO 10002	SZUTEST CO.

**TECHNICAL DATA****DIMENSIONS**

Width	29,89 mm
Height	64,26 mm
Depth	68,41 mm

ELECTRICAL DATA

Pin Range	5,08 mm/0,2 inch
Material Group	IIIa
Pollution Degree	2
Rated Current	16 A
Rated Voltage	250 V
Rated Impulse Voltage	4 kV

CONNECTION DATA

Conductor Connection Direction	90° - 180°
Solid Conductor	0,25...2,5 mm ² 23...14 AWG
Fine-Stranded Conductor	0,25...2,5 mm ² 23...14 AWG
Fine-Stranded Conductor With Ferules	0,25...1,5 mm ² 23...16 AWG
Stripping Length	7 mm

MATERIAL DATA

Insulation Material	PA66
Flammability Class Per	UL 94:V2
Screw Material	Chrome Zinc Stainles Steel (ZnCr)
Clamping Yoke	CK45 Steel
Pin&Contact Material	Brass
Pin&Contact Plating	Silver-Plated

MECHANICAL DATA

Screw	M2,5
Recommended Torque	0,40 Nm
Pin Dimensions	1x1 mm


ENVIRONMENTAL REQUIREMENTS

Operating Temperature Range	-40°C ... 100° C -40 ... + 212 ° F
-----------------------------	---------------------------------------

AVAILABLE PIN RANGES**2-12 PIN**

Can be multiplied up to the desired number of poles by interlocking.

TECHNICAL DRAWINGS



COMBINE PRODUCTS

5,08 mm SBDK-D (10.202-11.205-12.205)



5,08 mm SBDK-DD (10.252-11.255-12.255)



5,08 mm Multi-Color Modular Female (16.205)

